



FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7




FIG. 8




FIG. 9

LIGHTING REQUIREMENT		AVERAGE	MAX	MIN	DEFORMATION OF FILAMENT
BLINKING	CONTINUOUS ILLUMINATION	619.6	878.8	287.6	NONE
	(a) NO DIMMING	470.1	559.5	400.4	NONE
	DIMMING DURING EXTINCTION	2sec.	41.6	33.2	DEFORMED
		(b) 1sec.	274.8	114.7	DEFORMED
		0.5sec.	420.2	298.8	DEFORMED
(c) VOLTAGE SWITCHING	(d) STOPWISE DIMMING	486.6	638.5	393.3	NONE
	14/6V	254.3	499.0	79.6	DEFORMED
	14/7V	38.9	49.9	26.7	DEFORMED
	14/8V	18.9	25.7	6.2	DEFORMED
	14/9V	62.6	116.6	24.1	DEFORMED
	14/9.5V	250.0	280.0	138.9	SLIGHTLY DEFORMED
	14/10V	514.5	667.0	308.5	NONE AT THIS TIME

FIG. 10




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B

